

### SP-130-VP-SM 130mm Surface Mount Speaker Vandal Resistant

#### FEATURES

- ✓ Vandal resistant enclosure
- ✓ Dual loop in, loop out cable entries
- ✓ Steel front panel with di-cast enclosure
- ✓ Fitted with supervisory capacitor for line monitoring
- ✓ Tamper resistant torx screw fasteners
- ✓ High quality speaker driver developed for BGM, paging and emergency warning applications
- ✓ Fitted with 4 way wire protect terminal block for loop in, loop out wiring as required by Australian Standards
- ✓ Neutral RAL9016 powder-coated finish



#### PRODUCT DESCRIPTION

Designed to withstand the physical abuse of vandals.

Access to the 130mm twin cone speaker requires the use of a torx bit, minimising unauthorized tampering and/or theft.

Surface mounting enclosure features multiple conduit entries.

Recommended for use in prisons, train stations, bus stations, pedestrian malls, public housing etc.

#### TECHNICAL SPECIFICATIONS

Power Taps	0.25W, 0.75W, 1.5W, 3W, 6W
SPL 1W @ 1m	93dB @ 1kHz (+/- 2dB)
SPL Max	99dB @ full power octave bandwidth
Frequency Response	180Hz - 18kHz
Dispersion (1kHz/2kHz)	170° / 120°
Connection	4 way terminal block + 22uF bipolar capacitor
Dimensions	190mm W x 190mm H x 75mm D (140mm grill Ø)
Grill Material	Steel mesh grill
Weight	1.8kg
Operating Temperature	-15°C to +60°C