

PRODUCT DATA SHEET

ONESHOT (100dB) 200mm ONESHOT 100dB Range

FEATURES

- √ 100dB @ 1m @ 2.5W tapping
- √ High power output
- ✓ Excellent speech intelligibility
- High quality speaker driver developed for BGM, paging and emergency warning applications
- Patented 6 way latching ensures a neat, sag free installation
- Fitted with 4 way wire protect terminal block for loop in, loop out wiring as required by Australian Standards
- ✓ Fitted with supervisory capacitor for line monitoring
- ✓ High impact styrene grill





PRODUCT DESCRIPTION

The ONESHOT speaker range has excellent speech intelligibility and has been produced using a high fidelity twin cone driver, used for BGM and PA announcements.

These speakers come with a wide range of tappings from 0.33W to 5W. The patented 6 way latching clips ensure a fast fit application.

The 100dB output models of the ONESHOT range are available to mount directly to the underside of concrete slabs or inaccessible ceilings and are recommended for plantrooms, warehouses, shopping centres, etc.

Each speaker is fitted with an inline capacitor for use on 100V line PA systems for monitoring purposes.

A surface mount option (including both speaker and surface mount) is also available as a 100dB option.

TECHNICAL SPECIFICATIONS

	ONESHOT-200-100DB	ONESHOT-SUR-100DB
Power Taps	1.25W, 2.5W, 5W, 10W, 15W	
Sound Pressure Level	100dB @ 1kHz (±2dB) @ 1m @ 2.5W tapping	
Frequency Response	55Hz-15kHz	80Hz-12kHz
Connection	4 way terminal block + 22µF bipolar capacitor	
Grill Material	High impact styrene	
Dimensions	265mm Ø x 88mm D	310mm Ø x 85mm D
Ceiling Cut Out	246mm Ø	
Overall Weight	1.8kg	2kg
Colour	White	
Operating Temperature	-25°C to +55°C	
Relative Humidity	< 95%	





PRODUCT DATA SHEET

ONESHOT (100dB) 200mm ONESHOT 100dB Range

ORDERING INFORMATION

ONESHOT-200-100DB	200mm ONESHOT flush-mounted speaker + grill	
ONESHOT-SUR-100DB	200mm ONESHOT surface mounted speaker + grill	

Please note these speakers are not AS7240 approved.

