

FEATURES

- ✓ SSL approved
- ✓ Low profile design
- ✓ Optional tamper proof feature
- ✓ Two-wire loop connection
- ✓ Communication over +ve and -ve connections
- ✓ Remote indicator terminals



PRODUCT DESCRIPTION

Plug-in detector base for use with AFP-2800 & AFP-3030 Analog/Addressable fire alarm systems. Suitable for both Clip and FlashScan detectors. Base is also available in black.

TECHNICAL SPECIFICATIONS

Diameter	102mm
Mounting	50mm, 60mm and 70mm centres
Voltage Range	15 - 32Vdc
Standby Current (Nominal)	150µA at 24Vdc
Power-up Surge at Maximum Rated Voltage	1.5mA Sec
LED Current (Nominal)	6mA at 24Vdc
Size	18.8mm high (without detector)

ORDERING INFORMATION

SSF-BASE-IV	Ivory base to suit addressable detector range (B501AUS-IV)
SSF-BASE-W	White base to suit addressable detector range (B501AUS-W)
SSF-BASE-BK	Black base to suit addressable detector range (B501AUS)

APPROVALS

- ✓ ActivFire certified - Listing No. afp-1801 (AFP-2800)
- ✓ ActivFire certified - Listing No. afp-2976 (AFP-3030)